# Vickers Laboratories Ltd - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 2.1 Revision date: 16 April 2021 Date printed: 12 August 2023

**Section 1. Identification** 

1.1 Product Identifier 3147

Product Name KOVACS REAGENT

CAS Number Mixture

REACH Registration No A registration number is not available as the substance or its uses are exempt, the

annual tonnage does not require a registration or the registration is envisaged for a

later date.

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier Vickers Laboratories Ltd



Grangefield Industrial Estate

Richardshaw Road

Pudsey West Yorkshire LS28 6QW

UNITED KINGDOM

 Phone
 44 0113 2362811

 Fax
 +44(0)113 2362703

 Email
 safety@viclabs.co.uk

 Website
 www.viclabs.co.uk

**1.4 Emergency Telephone** (08:00-16:30) +44(0) 113 2362811

(24hr) 112

(Have this document to hand)

## Section 2. Hazards Identification

## 2.1 Classification of the substance or mixture

## Classification according to regulation 1272/2008/EC

Flammable liquid, category 3

Kin corrosion/irritation, category 2

Acute toxicity, category 4 (inhalation)

Serious eye damage/irritation, category 1

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H318: Causes serious eye damage.

Serious eye damage/irritation, category 1

Spec target organ tox - single, category 3

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

## 2.2 Label elements

### Labelling according to regulation 1272/2008/EC

Signal word Danger

Hazard Pictograms







Hazard Statements Flammable liquid and vapour. Harmful if inhaled. Causes serious eye damage. Causes skin irritation. May cause

respiratory irritation.

**Precautionary Statements** Keep container tightly closed. Wear protective gloves / protective clothing / eye protection / face protection.

Avoid breathing dust / fume / gas / mist / vapours / spray. IF SWALLOWED: Immediately call a POISON

CENTER or doctor/physician. Do NOT induce vomiting.

# Section 3. Composition

#### 3.1 Substances

Component	CAS No.	EEC No.	REACH No. Conc w/w		CLP Classification (1272/2008/CE)	
Amyl alcohol	Mixture	250-378-8		75%	Flam. Liq. 3,Skin Irrit. 2,Acute Tox. 4 (I),Eye Dam. 1,STOT SE 3 (I)	
Hydrochloric acid	7647-01-0	231-595-7	01-2119484862-27-XXXX	10%	Skin Corr. 1A,STOT SE 3 (I)	

# Section 4. First Aid

### 4.1 Description of first aid measures

Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION URGENTLY. Eyes

Skin Wash off skin thoroughly with water. Remove contaminated clothing immediately avoiding contamination of

unaffected areas.

Inhalation Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If

breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery

position. OBTAIN MEDICAL ATTENTION URGENTLY.

Ingestion If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen

if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Personal protection for first Wear protective gloves / eye protection.

aiders

## 4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

## Section 5. Fire Fighting

### 5.1 Extinguishing media

Extinguishing Media Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed

containers cool.

Unsuitable Media Do not use water jet.

## 5.2 Special hazards arising from the substance or mixture

Hazards Vapour-air mixtures are explosive.

### 5.3 Advice for firefighters

Advice for firefighters Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear

protective clothing and breathing apparatus.

# Section 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate

area immediately. Do not allow general use of area until it is safe to do so. Beware: vapour is heavier than air and

will tend to accumulate at low spots.

### 6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local

Environmental Health Officer if major spillage occurs.

#### 6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with

copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in

remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

#### 6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

# Section 7. Storage & Handling

### 7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

### 7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage. Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

### 7.3 Specific end use(s)

See section 1.2.

# Section 8. Workplace Exposure & Personal Protection

### 8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits				
			Long Term (8hr TWA)		Short Term 15min period)		
Amyl alcohol	Mixture	75%	100.0 ppm	125.0 mg/m-3	360.0 ppm	450.0 mg/m-3	
Hydrochloric acid	7647-01-0	10%	1.0 ppm	2.0 mg/m-3	5.0 ppm	8.0 mg/m-3	

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

### 8.2 Exposure controls

Respiratory Protection Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well

maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

# Section 9. Physical & Chemical Properties

# 9.1 Information on basic physical and chemical properties

Appearance Clear yellow solution.

Odour Pungent.

pΗ Not applicable **Boiling Point** 131°C Melting Point -117.2°C

Flash Point 42.8°C (Closed cup)

Upper Flammable Limit 9% Lower Flammable Limit 1.2% 350°C Auto Ignition **Explosive Properties** Slight. Oxidising Properties No.

Vapour Pressure 2.2501mmHg @ 20°C

Relative Density 1.0000 Water Solubility 3%

#### 9.2 Other information

No data available.

# Section 10. Stability & Reactivity

10.1 Reactivity No data available.

10.2 Chemical Stability Stable under normal conditions

10.3 Possibility of hazardous

reactions

No data available.

10.4 Conditions to Avoid Hot surfaces, naked flames or other sources of ignition.

**10.5** Incompatable Materials Acids. Strong oxidising agents.

None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide. Hazardous Decomposition

## Section 11. Toxicological Information

### 11.1 Information on toxicological effects

Eyes The liquid may cause severe irritation and corneal damage. High concentrations of vapour may cause severe

irritation.

Repeated or prolonged contact may defat the skin producing irritation and dermatitis. Liquid can be absorbed Skin

through intact skin. Very significant absorbtion can lead to collapse and may even prove fatal.

LD50 Skin 3970mg/kg Rabbit

Harmful if swallowed. Ingestion may cause central nervous system depression, leading to unconsciousness. Ingestion

Symptoms may include salivation, thirst, difficulty in swallowing, pain, shock and vomiting.

LD50 Oral

Exposure to vapour concentrations above the occupational exposure limits will produce irritation of the eyes and Inhalation

respiratory tract. High concentrations of vapour may effect the central nervous system acting as a narcotic.

LD50 Inhalation Not available **TCLo** Not available

Carcinogenicity Not considered to be a carcinogen. Mutagenicity Not considered to be a mutagen.

Reproductive Effects None identified.

# Section 12. Ecological

12.1 Toxicity Readily bio-degraded in the environment.

LC50 Algal Not available LC50 Crustacea Not available LC50 Fish Not available

12.2 Persistence and

degradability

No data available.

**12.3** Bioaccumulative potential No data available. 12.4 Mobility in soil No data available.

12.5 Results of PBT & vPvB

assessment

Assessment not required.

Other adverse effects None known at present.

## **Section 13. Disposal Considerations**

#### 13.1 Waste treatment methods

Disposal Methods Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of

into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

# Section 14. Transport Information

2920 14.1 UN Number

14.2 Proper Shipping Name Corrosive liquid, flammable, N.O.S. (Amyl

Alcohol, Hydrochloric Acid)

14.3 Transport classes

8 UN classification 3 Subsidiary hazard(s) Transport category 2 ADR Hazard ID 83 D/E Tunnel Restriction Code

14.4 Packing Group

14.5 Environment hazards See section 12.

No special precautions required. 14.6 Special precautions for

user

14.7 Transport in bulk Not transported in bulk.



15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification Flammable liquid, category 3; Skin corrosion/irritation, category 2; Acute toxicity, category 4 (inhalation); Serious

eye damage/irritation, category 1; Spec target organ tox - single, category 3

Signal word Danger

Hazard Pictograms







CORROSIVE

Hazard Statements H226, H332, H318, H315, H335

Flammable liquid and vapour. Harmful if inhaled. Causes serious eye damage. Causes skin irritation. May cause

respiratory irritation.

**Precautionary Statements** P233, P280, P261, P301+P310, P331

Keep container tightly closed. Wear protective gloves / protective clothing / eye protection / face protection.

Avoid breathing dust / fume / gas / mist / vapours / spray. IF SWALLOWED: Immediately call a POISON

CENTER or doctor/physician. Do NOT induce vomiting.

### 15.2 Chemical safety assessment

Assessment not required.

# Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 2.1 (Supercedes revision 2.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 12 August 2023

Copyright: 2023 Vickers Laboratories Ltd