Vickers Laboratories Ltd - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 2.0 Revision date: 19 April 2021 Date printed: 12 August 2023 (Replaces revision 1.1 of 16 April 2021)

Section 1. Identification

Product Identifier 1519

> Product Name WHITE SPIRIT

CAS Number 8052-41-3

REACH Registration No A registration number is not available as the substance or its uses are exempt, the

annual tonnage does not require a registration or the registration is envisaged for a

later date.

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier Vickers Laboratories Ltd

ICKERS

Grangefield Industrial Estate

Richardshaw Road

Pudsey West Yorkshire LS28 6QW

UNITED KINGDOM

Phone 44 0113 2362811 Fax +44(0)113 2362703 Email safety@viclabs.co.uk Website www.viclabs.co.uk

Emergency Telephone (08:00-16:30) +44(0) 113 2362811

(24hr)

(Have this document to hand)

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to regulation 1272/2008/EC

Flammable liquid, category 3 Skin corrosion/irritation, category 2

Spec target organ tox - repeat, category 1

Aspiration hazard, category 1

Hazard to aquatic environment, category 3

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H372: Causes damage to organs through prolonged or repeated exposure.

H304: May be fatal if swallowed and enters airways.

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to regulation 1272/2008/EC

Signal word Danger

Hazard Pictograms







Hazard Statements Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes

damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

Precautionary Statements Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective

clothing / eye protection / face protection. Store in a well ventilated place. Keep cool. Avoid release to the

environment.

Section 3. Composition

3.1 Substances

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
White spirit	8052-41-3	265-191-7		>99.5%	Flam. Liq. 3,Skin Irrit. 2,STOT RE 1,Asp. Tox. 1,Aquatic Chronic 3

Section 4. First Aid

4.1 Description of first aid measures

Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL Eyes

Skin Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. In

severe cases or if exposure has been great, OBTAIN MEDICAL ATTENTION.

Inhalation Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If

breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Ingestion If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen

if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the

recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Personal protection for first Wear protective gloves / eye protection.

aiders

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media

Extinguishing Media Water spray, foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.

Unsuitable Media Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards Vapour-air mixtures are explosive.

5.3 Advice for firefighters

Advice for firefighters Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear

protective clothing and breathing apparatus.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate

area immediately. Do not allow general use of area until it is safe to do so. Beware: vapour is heavier than air and

will tend to accumulate at low spots.

6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local

Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with

copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in

remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage. Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents. Large quantities must be stored in accordance with the Petroleum Spirits Act.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits			
			Long Term (8hr TWA)		Short Term 15min period)	
White spirit	8052-41-3	>99.5%	100.0 ppm	125.0 mg/m-3	575.0 ppm	720.0 mg/m-3

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance Clear colourless liquid.

Odour Characteristic.
pH Not applicable
Boiling Point 165°C
Melting Point Not applicable

Vickers Laboratories Ltd - Safety Data Sheet Ref: 1519 Page 3 of 6

Flash Point 52°C (Closed cup)

Upper Flammable Limit
Lower Flammable Limit
Auto Ignition

8%
0.6%
240°C

Explosive Properties Severe in confined spaces.

Oxidising Properties No.

Vapour Pressure 1.9mmHg @ 20°C

Relative Density 0.7830

Water Solubility Insoluble in water.

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1 Reactivity No data available.

10.2 Chemical Stability Stable under normal conditions

10.3 Possibility of hazardous

reactions

No data available.

10.4 Conditions to Avoid Hot surfaces, naked flames or other sources of ignition.

10.5 Incompatable Materials Strong oxidising agents.

10.6 Hazardous Decomposition None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

Products

Section 11. Toxicological Information

11.1 Information on toxicological effects

Eyes Both the vapour and liquid may, act as an eye irritant.

Skin The liquid is mildly irritating to the skin. Repeated or prolonged contact may defat the skin producing irritation

and dermatitis.

LD50 Skin 3400mg/kg Rabbit

Ingestion Ingestion will cause causes damage to stomach and intestinal linings.

LD50 Oral 15000mg/kg Rat

Inhalation Exposure to vapour concentrations above the occupational exposure limits will cause narcosis. Prolonged

exposure to vapour concentrations above the occupational exposure limits will cause headache, nausea, vomiting and irritation of the mucous membranes. High concentrations of vapour may produce central nervous system

depression and unconsciousness. Causes damage to the central nervous system through this route.

LD50 Inhalation 13.1mg/l Rat
TCLo Not available

Carcinogenicity Not considered to be a carcinogen.

Mutagenicity Not considered to be a mutagen.

Reproductive Effects No information is available.

Section 12. Ecological

12.1 Toxicity Expected to be toxic to aquatic life if discharged to natural waters.

LC50 Algal 10-22 mg/l Daphnia magna (48 hours)

LC50 Crustacea Not available

LC50 Fish ~10 - 30 mg/l Rainbow Trout (96 hours)

12.2 Persistence and No data available.

degradability

12.3 Bioaccumulative potential No data available.

12.4 Mobility in soil No data available.

12.5 Results of PBT & vPvB Assessment not required.

assessment

Ref: 1519

Section 13. Disposal Considerations

13.1 Waste treatment methods

Disposal Methods Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of

into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

Section 14. Transport Information

14.1 UN Number 1300

14.2 Proper Shipping Name Turpentine substitute

14.3 Transport classes

UN classification 3
Subsidiary hazard(s) None
Transport category 3
ADR Hazard ID 30
Tunnel Restriction Code D/E

14.4 Packing Group III

14.5 Environment hazards See section 12.

14.6 Special precautions for

No special precautions required.

user

14.7 Transport in bulk Not transported in bulk.

Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification Flammable liquid, category 3; Skin corrosion/irritation, category 2; Spec target organ tox - repeat, category 1;

Aspiration hazard, category 1; Hazard to aquatic environment, category 3

Signal word Danger

Hazard Pictograms







Hazard Statements H226, H304, H315, H372, H412

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

Hazard Statements (Packs of 500ml/g or less)

H226, H304, H411

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Toxic to aquatic life with long

lasting effects.

Precautionary Statements P210, P280, P403+P235, P273

Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing / eye protection / face protection. Store in a well ventilated place. Keep cool. Avoid release to the

environment.

Precautionary Statements (Packs of 500ml/g or less)

P210, P280, P403+P235

Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing / eye protection / face protection. Store in a well ventilated place. Keep cool.

15.2 Chemical safety assessment

Assessment not required.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 2.0 (Supercedes revision 1.1)

Revision date: 19 April 2021

Reviewed by chemist: 19 April 2021

Printed date: 12 August 2023

Copyright: 2023 Vickers Laboratories Ltd