

Revision: 2.1

Revision date:

16 April 2021

Date printed:

12 August 2023

## Section 1. Identification

### 1.1 Product Identifier 1623

Product Name PARAFFIN OIL (LOW SULPHUR)

CAS Number 64742-81-0

REACH Registration No A registration number is not available as the substance or its uses are exempt, the annual tonnage does not require a registration or the registration is envisaged for a later date.

### 1.2 Relevant identified uses of the substance or mixture & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

### 1.3 Supplier Vickers Laboratories Ltd



Grangefield Industrial Estate  
Richardshaw Road  
Pudsey  
West Yorkshire  
LS28 6QW  
UNITED KINGDOM

Phone 44 0113 2362811  
Fax +44(0)113 2362703  
Email [safety@viclabs.co.uk](mailto:safety@viclabs.co.uk)  
Website [www.viclabs.co.uk](http://www.viclabs.co.uk)

### 1.4 Emergency Telephone (08:00-16:30) +44(0) 113 2362811 (24hr) 112 (Have this document to hand)

## Section 2. Hazards Identification

### 2.1 Classification of the substance or mixture

#### Classification according to regulation 1272/2008/EC

|  |  |
|--|--|
| Flammable liquid, category 3               | H226: Flammable liquid and vapour.                     |
| Skin corrosion/irritation, category 2      | H315: Causes skin irritation.                          |
| Spec target organ tox - single, category 3 | H336: May cause drowsiness or dizziness.               |
| Aspiration hazard, category 1              | H304: May be fatal if swallowed and enters airways.    |
| Hazard to aquatic environment, category 2  | H411: Toxic to aquatic life with long lasting effects. |

### 2.2 Label elements

#### Labelling according to regulation 1272/2008/EC

Signal word Danger

Hazard Pictograms



**Hazard Statements** Flammable liquid and vapour. Causes skin irritation. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

**Precautionary Statements** IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing / eye protection. Store in a well ventilated place. Keep cool.

## Section 3. Composition

### 3.1 Substances

| Component                 | CAS No.    | EEC No.   | REACH No. | Conc w/w | CLP Classification (1272/2008/CE)  |
|---------------------------|------------|-----------|-----------|----------|--|
| Mixed hydrocarbon solvent | 64742-81-0 | 265-184-9 |           | >99.5%   | Flam. Liq. 3, Skin Irrit. 2, STOT SE 3 (D), Asp. Tox. 1, Aquatic Chronic 2 |

## Section 4. First Aid

### 4.1 Description of first aid measures

|                                      |   |
|--------------------------------------|---|
| Eyes                                 | Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION.   |
| Skin                                 | Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. In severe cases or if exposure has been great, OBTAIN MEDICAL ATTENTION.  |
| Inhalation                           | Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.                        |
| Ingestion                            | If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY. |
| Personal protection for first aiders | Wear protective gloves / eye protection.  |

### 4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

## Section 5. Fire Fighting

### 5.1 Extinguishing media

|                     |  |
|---------------------|--|
| Extinguishing Media | Water spray, foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool. |
| Unsuitable Media    | Do not use water jet.  |

### 5.2 Special hazards arising from the substance or mixture

|         |                                    |
|---------|------------------------------------|
| Hazards | Vapour-air mixtures are explosive. |
|---------|------------------------------------|

### 5.3 Advice for firefighters

|                         |  |
|-------------------------|--|
| Advice for firefighters | Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus. |
|-------------------------|--|

## Section 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so. Beware : vapour is heavier than air and will tend to accumulate at low spots.

### 6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.

### 6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

### 6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

## Section 7. Storage & Handling

### 7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

### 7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents. Large quantities must be stored in accordance with the Petroleum Spirits Act.

### 7.3 Specific end use(s)

See section 1.2.

## Section 8. Workplace Exposure & Personal Protection

### 8.1 Control parameters

| Component                 | CAS No     | Concentration | Workplace Exposure Limits |                         |
|---------------------------|------------|---------------|---------------------------|-------------------------|
|                           |            |               | Long Term (8hr TWA)       | Short Term 15min period |
| Mixed hydrocarbon solvent | 64742-81-0 | >99.5%        | -                         | -                       |

Exposure data source(s) No occupational exposure data currently available.

### 8.2 Exposure controls

Respiratory Protection Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Eye Protection Use tightly fitting chemical splash proof glasses or goggles.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

## Section 9. Physical & Chemical Properties

### 9.1 Information on basic physical and chemical properties

Appearance Pale yellow liquid.  
Odour Characteristic.  
pH Not applicable  
Boiling Point 140°C

|                       |                                     |
|-----------------------|-------------------------------------|
| Melting Point         | Not applicable                      |
| Flash Point           | 38°C (Closed cup)                   |
| Upper Flammable Limit | 5%                                  |
| Lower Flammable Limit | 0.7%                                |
| Auto Ignition         | 230°C                               |
| Explosive Properties  | Moderate/severe in confined spaces. |
| Oxidising Properties  | No.                                 |
| Vapour Pressure       | Not applicable                      |
| Relative Density      | 0.8000                              |
| Water Solubility      | Insoluble in water.                 |

## 9.2 Other information

No data available.

## Section 10. Stability & Reactivity

|   |  |
|---|--|
| 10.1 Reactivity                         | No data available.   |
| 10.2 Chemical Stability                 | Stable under normal conditions   |
| 10.3 Possibility of hazardous reactions | No data available.   |
| 10.4 Conditions to Avoid                | Hot surfaces, naked flames or other sources of ignition.                         |
| 10.5 Incompatible Materials             | Strong oxidising agents.   |
| 10.6 Hazardous Decomposition Products   | None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide. |

## Section 11. Toxicological Information

### 11.1 Information on toxicological effects

|                      |   |
|----------------------|---|
| Eyes                 | Both the vapour and liquid will, act as an eye irritant. Repeated exposure to the vapours can lead to reversible corneal changes and conjunctivitis   |
| Skin                 | The liquid is mildly irritating to the skin. Repeated or prolonged contact may defat the skin producing irritation and dermatitis.  |
| LD50 Skin            | >2000 mg/Kg Rabbit  |
| Ingestion            | Ingestion will cause causes damage to stomach and intestinal linings.   |
| LD50 Oral            | >5000 mg/Kg Rat   |
| Inhalation           | Exposure to vapour concentrations above the occupational exposure limits will cause narcosis. Prolonged exposure to vapour concentrations above the occupational exposure limits will cause headache, nausea, vomiting and irritation of the mucous membranes. High concentrations of vapour may produce central nervous system depression and unconsciousness. |
| LD50 Inhalation      | >5.28 mg/L Rat  |
| TCLo                 | Not available   |
| Carcinogenicity      | Not considered to be a carcinogen.  |
| Mutagenicity         | Not considered to be a mutagen.   |
| Reproductive Effects | Not teratogenic but can be toxic to the embryo and foetus and may result in reduced fertility.  |

## Section 12. Ecological

|                                    |   |
|------------------------------------|---|
| 12.1 Toxicity                      | Low order of toxicity: LC50,96hr, fish >1000ppm; EC50, 24hr, Daphnia >250ppm; IC50, 72hr, Algae =20ppm. |
| LC50 Algal                         | Not available   |
| LC50 Crustacea                     | Not available   |
| LC50 Fish                          | Not available   |
| 12.2 Persistence and degradability | No data available.  |
| 12.3 Bioaccumulative potential     | No data available.  |
| 12.4 Mobility in soil              | No data available.  |

12.5 Results of PBT & vPvB assessment      Assessment not required.

12.6 Other adverse effects      None known at present.

## Section 13. Disposal Considerations

### 13.1 Waste treatment methods

Disposal Methods      Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging      Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

## Section 14. Transport Information

14.1 UN Number      1223

14.2 Proper Shipping Name      Kerosene

14.3 Transport classes

UN classification      3

Subsidiary hazard(s)      None

Transport category      3

ADR Hazard ID      30

Tunnel Restriction Code      D/E

14.4 Packing Group      III

14.5 Environment hazards      See section 12.

14.6 Special precautions for user      No special precautions required.

14.7 Transport in bulk      Not transported in bulk.



## Section 15. Regulatory Information

### 15.1 Safety, health and environment regulations specific for substance/mixture.

#### Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification      Flammable liquid, category 3; Skin corrosion/irritation, category 2; Spec target organ tox - single, category 3; Aspiration hazard, category 1; Hazard to aquatic environment, category 2

Signal word      Danger

Hazard Pictograms



Hazard Statements      H226, H315, H304, H336, H411  
Flammable liquid and vapour. Causes skin irritation. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

Precautionary Statements      P301+P310, P331, P210, P280, P403+P235  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing / eye protection. Store in a well ventilated place. Keep cool.

### 15.2 Chemical safety assessment

Assessment not required.

## Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 2.1 (Supercedes revision 2.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 12 August 2023

Copyright: 2023 Vickers Laboratories Ltd