Vickers Laboratories Ltd - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.1

Revision date: Date printed: 16 April 2021 12 August 2023

3086

Section 1. Identification

Product Identifier	3086
Product Name	DECANEDIOYL DICHLORIDE SOLN 5% w/w in cyclohexane
CAS Number REACH Registration No	110-82-7 A registration number is not available as the substance or its uses are exempt, the annual tonnage does not require a registration or the registration is envisaged for a later date.
Molecular Formula	CH ₂ (CH ₂) ₄ CH ₂ =84.16

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier

1.4

1.1

Vickers Laboratories Ltd



Grangefield Industrial Estate Richardshaw Road Pudsey West Yorkshire LS28 6QW UNITED KINGDOM

Phone Fax Email Website	44 0113 2362811 +44(0)113 2362703 safety@viclabs.co.uk www.viclabs.co.uk	
Emergency Telephone	(08:00-16:30) +44(0) 113 2362811	
	(24hr) 112	
	(Have this document to hand)	

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to regulation 1272/2008/EC

Flammable liquid, category 2	H225: Highly flammable liquid and vapour.
Skin corrosion/irritation, category 2	H315: Causes skin irritation.
Spec target organ tox - single, category 3	H336: May cause drowsiness or dizziness.
Aspiration hazard, category 1	H304: May be fatal if swallowed and enters airways.
Hazard to aquatic environment, category 1	H400: Very toxic to aquatic life.
Hazard to aquatic environment, category 1	H410: Very toxic to aquatic life with long lasting effects.


2.2 Label elements

Labelling according to regulation 1272/2008/EC

Danger

Signal word

Hazard Pictograms



Section 3. Composition

3.1 Substances

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Cyclohexane	110-82-7	203-806-2	01-2119463273-41-XXXX	95%	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3 (D), Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1
Sebacoyl chloride	111-19-3	203-843-4		5%	Acute Tox. 2 (D), Skin Corr. 1B, Acute Tox. 4 (O)
				270	

Section 4. First Aid

4.1 Description of first aid measures

Eyes	Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. If discomfort persists OBTAIN MEDICAL ATTENTION.
Skin	Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. OBTAIN MEDICAL ATTENTION.
Inhalation	Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Ingestion	If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Personal protection for first aiders	Wear protective gloves / eye protection.

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media

Extinguishing Media Alcohol resistant foam, dry powder, carbon dioxide or vaporising liquid. Use water spray to keep fire exposed containers cool.

Unsuitable Media Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards

Vapour-air mixtures are explosive.

5.3 Advice for firefighters

Advice for firefighters

Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection	Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so. Beware : vapour is heavier than air and
	will tend to accumulate at low spots.

6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

- Major SpillageContain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with
copious amounts of water.Minor SpillageContain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with
 - inor Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits			
			Long Term (8hr TWA)	Short Term 15	min period)
Cyclohexane	110-82-7	95%	100.0 ppm	300.0 mg/m-3	350.0 ppm	1050.0 mg/m-3
Sebacoyl chloride	111-19-3	5%	-	1.0 mg/m-3	-	5.0 mg/m-3

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

Respiratory Protection	Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.
Hand Protection	Use solvent resistant gloves.
Eye Protection	Use tightly fitting chemical splash proof glasses or goggles.
Skin Protection	Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.
Special Hazards	No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance	Clear colourless liquid
Odour	Characteristic.

Not applicable pН Boiling Point 80.7°C Melting Point 6.5°C Flash Point -18°C (Closed cup) Upper Flammable Limit 8% Lower Flammable Limit 1.3% Auto Ignition 260°C **Explosive Properties** Severe in confined spaces. **Oxidising Properties** No. Vapour Pressure 100mmHg @ 61°C **Relative Density** 0.8000 Water Solubility Decomposes in water.

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1	Reactivity	No data available.
10.2	Chemical Stability	Stable under normal conditions
10.3	Possibility of hazardous reactions	No data available.
10.4	Conditions to Avoid	Hot surfaces, naked flames or other sources of ignition.
10.5	Incompatable Materials	Strong oxidising agents. Inter halogen compounds eg.bromide tri and pentafluoride, iodine penta and heptafluorides etc.
10.6	Hazardous Decomposition Products	None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

Section 11. Toxicological Information

11.1 Information on toxicological effects

U	
Eyes	Both the vapour and liquid are, irritating to the eyes.
Skin	Repeated or prolonged contact may defat the skin producing irritation and dermatitis.
LD50 Skin	Not available
Ingestion	May be fatal if swallowed and enters airways.
LD50 Oral	Not available
Inhalation	Exposure to vapour concentrations above the occupational exposure limits may produce irritation of the eyes and respiratory tract. High concentrations of vapour will cause narcosis, anaesthesia and fatigue.
LD50 Inhalation	Not available
TCLo	Not available
Carcinogenicity	Not considered to be a carcinogen.
Mutagenicity	Not considered to be a mutagen.
Reproductive Effects	None identified.

Section 12. Ecological

12.1	Toxicity	Moderately toxic to mammals, fish and bacteria. Very Toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment.
	LC50 Algal	Not available
	LC50 Crustacea	Not available
	LC50 Fish	Not available
12.2	Persistence and degradability	No data available.
12.3	Bioaccumulative potential	No data available.
12.4	Mobility in soil	No data available.

Vickers Laboratories Ltd - Safety Data Sheet

Ref: 3086

- **12.5** Results of PBT & vPvB Assessment not required. assessment
- **12.6** Other adverse effects None known at present.

Section 13. Disposal Considerations

13.1 Waste treatment methods

Disposal Methods Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

Section 14. Transport Information

14.1	UN Number	1145	
14.2	Proper Shipping Name	Cyclohexane	
14.3	Transport classes UN classification Subsidiary hazard(s) Transport category ADR Hazard ID	3 None 2 33	FLAMMABLE LIQUID
14.4	Tunnel Restriction Code Packing Group	D/E II	
	Environment hazards	See section 12.	
14.6	Special precautions for user	No special precautions required.	
14.7	Transport in bulk	Not transported in bulk.	

Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification	Flammable liquid, category 2; Skin corrosion/irritation, category 2; Spec target organ tox - single, category 3; Aspiration hazard, category 1; Hazard to aquatic environment, category 1; Hazard to aquatic environment, category 1	
Signal word	Danger	
Hazard Pictograms		
Hazard Statements	H225, H304, H315, H336, H410 Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Very toxic to aquatic life with long lasting effects.	
Precautionary Statements	P233, P280, P261, P301+P310, P331 Keep container tightly closed. Wear protective gloves / protective clothing / eye protection / face protection. Avoid breathing dust / fume / gas / mist / vapours / spray. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.	
Chamical speak associated as a second state of the		

15.2 Chemical safety assessment

Assessment not required.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.1 (Supercedes revision 1.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 12 August 2023

Copyright: 2023 Vickers Laboratories Ltd